

Technical Data Sheet

CODE 11333

MEX 120/5" LL 1S

Wall axial fans




Certifications



TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Weight (Kg)	0,77
Insulation Class	II°	Max delivery at max speed (l/s)	48,6
IP	45	Max delivery at max speed (m³/h)	175
Max ambient temperature for continuous operation (°C)	50	Pressure max - max speed (mmH2O)	5
Max. absorbed Current at max. speed (A)	0,095	Pressure max - max speed (Pa)	49,04
Max. absorbed power at max speed (W)	13	RPM max	2075
Nominal Diameter (mm)	120	Sound power Lw [dB(A)] - max speed	52,8
Voltage (V)	220-240	Sound pressure level Lp in free field [dB(A)] 3 m max speed	32,3

DIMENSIONS



Etichetta Energetica	NO
Size A (mm)	193
Size B (mm)	193
Size C (mm)	138
Size D (mm)	Ø 119
Size E (mm)	71
Size F (mm)	53
Size G (mm)	152
Size H (mm)	152
Size L (mm)	Ø 3,5

Technical Data Sheet

CODE 11333

MEX 120/5" LL 1S

Wall axial fans



DESCRIPTION

- Housings made of shockproof and UV resistant white ABS.
- Nominal diameter 120 mm.
- AC motor equipped with long-life ball-bearings, mixed-flow impellers made of PP resistant to aggressive substances.
- Maximum air flow 175 m³/h.
- Integrated butterfly back-draught shutter designed to prevent unwanted air inflows when the appliance is switched-off.
- Protection rating IP45, suitable for installation in Zone 1 of bathrooms, as defined by international standard IEC 60364-7.
- IMQ safety certification.

CURVES

□